

ECU-1152

TI Cortex A8 Industrial Communication Gateway with 2 x LAN and 6 x COM Ports

NEW



Introduction

For solar power, electricity, and factory-related applications that require comprehensive wireless and Ethernet communication solutions, Advantech developed its ECU-1152 RISC-based industrial communication gateway. ECU-1152 features an open platform design with a Cortex A8 processor, six RS-232/485 isolated serial ports, two 10/100 Ethernet ports, and an operating temperature of -40 ~ 70°C. ECU-1152 is equipped with a Linux operating system and open TagLink SDK to enable system integrators to develop applications specific for their application requirements.

Specifications

General

- Certification** CE, FCC
- Mounting** Wall/ DIN rail
- Power Consumption** 2.4W @ 24V_{DC} (typical)
- Power Requirements** 10 ~ 30 V_{DC}

System

- CPU** TI Cortex A8, 800MHz
- Memory** DDR3L 512MB
- Indicators** Programmable LEDs for Power, LAN (LINK, ACT), Serial (Tx, Rx)
- Storage** 1 GB Micro SD card for system storage
- SD Slot** 1 x Micro SD
- Watchdog** Yes
- Real-Time Clock** Yes
- Node ID** 8-bit

Communication

- Serial Port** 6 x RS-232/485
- Serial Port Speed** Isolation 3000 V_{DC}
- Ethernet Port** RS-232/RS-485: 50 ~ 115.2 kbps
- USB Port** 2 x 10/100 Base-T RJ-45 ports
- Wireless (Optional)** 1 x USB
- Interface: 1x Mini PCIe (full size)
- Type: Wi-Fi/3G/GPRS/4G
- Signal: USB

Software

- OS Support** RTLinux 3.12
- Configuration Tool** Advantech TagLink Studio
- Protocol Support** Modbus, IEC-60870
- Programming** Linux C
- PLC driver Support** Mitsubishi, Siemens, Omron, Delta

Environment

- Operating Temperature** -40 ~ 70°C
- Storage Temperature** -40 ~ 85°C
- Humidity** 5 ~ 95% (non-condensing)

Features

- TI Cortex A8 800 MHz CPU
- DDR3L 512 MB RAM
- 1 GB Micro SD card for system storage
- 1 x Micro SD slot
- 6 x RS-232/485 isolated serial ports
- 2 x 10/100 Base-T Ethernet ports
- 1 x Mini PCIe for Wi-Fi/3G/GPRS/4G
- Supports web access for remote online monitoring
- Supports Micro-SD cards and online firmware updates
- Supports Modbus and IEC-60870 protocol
- Supports data logging to Micro-SD card
- RTLinux operating system
- 40 ~ 70°C operating temperature range

Ordering Information

- ECU-1152-R11ABE** TI Cortex A8 industrial communication gateway with 2 x LAN, 6 x COM, 1 x Mini PCIe
- EIS-FMC251-T1152A** ECU-1152 w/ TagLink SW
- 1950020136T001** DIN-Rail buckle

Wi-Fi Solution

- 9656EWMG00E** Half to full-size Mini PCIe bracket pack
- EWM-W150H02E** Half-size mini card, supports 802.11bgn
- 1750006043** SMA(M) cable, 15 cm
- 1750000318** 2dBi antenna for testing, 11 cm

3G/GPRS Solution (SIM card not included)

- EWM-C109F601E** 6-band HSPA cellular module with SIM holder
- 1750006264** SMA(F) cable, 15 cm
- 1750005865** Dipole antenna, 11 cm

Storage Solution

- 96FMMMSDI-4G-ET-AT1** ATP 4G MICRO SD CARD I-GRD SLC(G)
- 96FMMMSDI-8G-ET-AT1** ATP 8G MICRO SD CARD I-GRD SLC(G)

Dimensions

